

SP-BT530 Wall Mount Speaker



Features:

Model Number: SP-BT530

- **Output Power: 30Wx2@8Ω**
- **Input Sensitivity: 0.5V**
- **Frequency Response: 60Hz-18KHz/1W,±0.5dB**
- **Harmonic Distortion: 20Hz-20KHz/1W,0.05%**
- **Damping Coefficient: >200@8Ω/400Hz**
- **Conversion Rate: 30V/US**
- **Channel Separation: >75dB(without weighting)**
- **S/N: >95dB(without weighting)**
- **Amplifier: Class D digital amplifier**
- **Indication: Power, channel signal indication**
- **Protection: Over temperature protection, overload protection, mute and switch**
- **Input: AV lotus seat, 6.5 socket, plug-in terminal**
- **Power supply: AC110V-240V/50Hz-60Hz**
- **Dimension: 170*185*250mm**

Specification:

| | |
|----------------------------|------------------------------------|
| Output Power | 30Wx2@8Ω |
| Input Sensitivity | 0.5V |
| Frequency Response | 60Hz-18KHz/1W,±0.5dB |
| Harmonic Distortion | 20Hz-20KHz/1W,0.05% |
| Dimension | 170*185*250mm |
| S/N | >95dB(without weighting) |
| Amplifier | Class D digital amplifier |