

SP-BT63 Ceiling Speaker



Features:

- Stereo wireless Blue-tooth transmission solution, BEKEN's BK8000L chip provides high quality sound quality and compatibility for the module, overall performance is superior;
- Comes with 1 channel 3.5 jack stereo local audio input;
- AC110V~AC220V power supply mode;;
- Reasonable structure, beautiful appearance, ceiling-mounted installation;
- Full-band speaker unit with a wide frequency response;
- High performance, low distortion, low loss;
- Wireless transmission range is more than 10 meters;
- Rated power:4*10W/Class D digital power amplifier module;
- Frequency response: 120Hz-15KHz ($\pm 3\text{dB}$) ;
- Nonlinear distortion THD: <0.05% at 1kHz, 1/3 rated output power;
- Signal to noise ratio S/N: >70dB;
- Support Blue-tooth protocol: HFPV1.5, A2DPV1.2, AVRCPV1.4, HSP1.2, GAVDP1.2, IOP;
- Speaker unit: Integration 6" Dual Cone Ceiling Speaker;
- Power consumption: 25W;
- Installation: Ceiling mount;
- Decorative materials: ABS;
- Power supply: AC110V~AC220V $\pm 10\%$ 50-60Hz;
- Case size: $\Phi 185 \times 60\text{mm}$;
- Opening hole size: $\Phi 170\text{mm}$;
- Weight: 1.6kg(2 pcs);

Specification:

| item | value |
|---------------------------|--|
| Place of Origin | China |
| | Guangdong |
| Brand Name | SURPASS |
| Model Number | BT63 |
| Warranty | 3months-1year |
| Customized | Yes |
| Shell Material | Plastic |
| The body material | Plastic |
| Rated power | 4*10W |
| Frequency response | 120Hz-15KHz($\pm 3\text{dB}$) |
| Nonlinear distortion THD | <0.05% at 1kHz,1/3 rated output power |
| Signal to noise ratio S/N | >70dB |
| Speaker unit | Integration 6" Dual Cone Ceiling Speaker |
| Power consumption | 25W |
| Installation | Ceiling mount |
| Decorative materials | ABS |
| Power supply | AC110V~AC220V $\pm 10\%$ 50-60Hz |
| Weight | 1.6kg(2 pcs) |