

SP-SD4300 Power Amplifier



Features:

Input Type: Balanced Dragon Input Input Sensitivity: 770mV Output Impedance: 8Ω/4Ω Frequency response: 20Hz-20KHz (1KHz/≤0.1%THD) Signal-to-noise ratio: >92dB Channel separation: >50dB Input Mode: Stereo, Signal Parallel, Output Bridge Protection type: boot delay, boot soft start, over current compression, short circuit, over temperature, input volume automatic compression Indicators: Power, Signal, Clip, Protect Input power: AC90V~240V, 50Hz/60Hz Aluminum Panel Production Dimension: 483*345*44mm Package Size: 540*410*60mm

Specifications:

item	value
Place of Origin	China
	Guangdong
Brand Name	SURPASS
Model Number	SD4300
Warranty	3months-1year
Customized	Yes
Input Type	Balanced Dragon Input
Input Sensitivity	770mV
Output Impedance	8 Ohm/4 Ohm
Frequency response	20Hz-20KHz (1KHz/≤0.1%THD)
Signal-to-noise ratio	>92dB
Channel separation	>50dB
Input Mode	Stereo, Signal Parallel, Output Bridge
Input power	AC90V~240V, 50Hz/60Hz
Indicators	Power, Signal, Clip, Protect
Production Dimension	483*345*44mm