

SP-BT62
Ceiling Speaker

 Bluetooth



Features:

- Frequency response: 120Hz-15KHz (±3dB) ;
- Nonlinear distortion THD: <0.05% at 1kHz, 1/3 rated output power;
- Signal to noise ratio S/N: >70dB;
- Support Blue-tooth protocol: HFPV1.5, A2DPV1.2,AVRCPV1.4, HSP1.2, GAVDP1.2, IOP;
- Speaker unit:Integration 6" Dual Cone Ceiling Speaker;
- Power consumption: 25W;
- Installation: Ceiling mount;
- Decorative materials: ABS;
- Power supply:AC110V~AC220V±10% 50-60Hz;
- Case size: Φ185x60mm; ▪ Opening hole size: Φ170mm;
- Weight: 1.6kg(2 pcs);

Specifications:

Model Number	BT62
Type	Active
Use	HOME THEATRE, Mobile Phone, COMPUTER
Place of Origin	China
	Guangdong
Power supply	AC110V~AC220V
Rated power	2*10W
Frequency response	120Hz-15KHz(±3dB)
Nonlinear distortion THD	<0.05% at 1kHz
Signal to noise ratio S/N	>70dB
Support Blue-tooth protocol	HFPV1.5, A2DPV1.2,AVRCPV1.4,HSP1.2, GAVDP1.2,IOP;
Speaker unit	Integration 6" Dual Cone Ceiling Speaker
Power consumption	25W
Decorative materials	ABS
Weight	1.6kg(2 pcs)