

SP-BTF52 Ceiling Speaker

Master + Slave
Blue-tooth CEILING SPEAKER



Features:

• Rated Power: 2x50W • Peak Power: 2x100W • Frequency Response: 50Hz-22KHz • Impedance: 8Ω • Sensitivity: 90dB±3dB • Speaker Unit: Integration 8"Coaxial unit • Blue-tooth Version: 5.1, Wireless transmission range is more than 10 meters • Amplifier: Class D digital power amplifier module • Nonlinear Distortion THD: <0.05% at 1kHz, 1/3 rated output power • S/N: >82dB • Power Supply: AC110V~AC220V±10% 50-60Hz • Installation: Ceiling mount • Decorative Materials: ABS • Product size: 280*100mm • Opening hole size: Φ250mm • Weight: 4kg

Specifications:

| | |
|----------------------|---|
| Model Number | BTF52 |
| Type | Active |
| Use | HOME THEATRE, Hotel |
| Channels | 2 |
| Place of Origin | China |
| | Guangdong |
| Rated Power | 2x50W |
| Peak Power | 2x100W |
| Frequency Response | 55-22Khz |
| Impedance | 8 Ohm |
| Sensitivity | 90dB |
| Amplifier Module | Built-in Class D digital power amplifier module |
| Speaker Unit | Integration 8"Coaxial unit |
| Installation | Ceiling mount |
| Dimension | d280x108mm |
| Decorative Materials | ABS |